

Avide LED Flood Light Slim SMD 20W NW 4000K

Product code:	ABSSFLNW-20W
Brand link:	avidelighting.com/qr/ABSSFLNW-20W
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kisatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-05-21

Page: 1/3

SPECIFICATIONS

EAN code:	5999097908922
Warranty:	3year(s)
Working temperature:	-20 - +40 °C
Packaging:	1/b 40/c 1200/p
Certifications:	CE

TECHNICAL DETAILS

Wattage:	20W
Voltage:	220-240V
Beam angle:	120°
Dimmability:	No
Lumen output:	1 600lm
Color temperature:	4 000K
Lifetime:	25 000h
Energy class:	F
Type of LED:	SMD
Driver:	Linear IC
CRI:	>80
IP standard:	IP65

BOX PICTURE



Avide LED Flood Light Slim SMD 20W NW 4000K

Product code: ABSFLNW-20W
Brand link: avidelighting.com/qr/ABSFLNW-20W
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-21
Page: 2/3

PRODUCT SIZE

Width: 112mm
 Height: 77mm
 Depth: 33mm

CARDBOARD BOX

EAN: 5999097908922
 Packaging: 1/b 40/c 1200/p
 Dimensions: 95mm x 135mm x 50mm
 Net weight: 307.3g
 Gross weight: 317.5g

CARTON

EAN: 5999097908939
 Packaging: 1/b 40/c 1200/p
 Dimensions: 550mm x 320mm x 220mm
 Net weight: 12.2936kg
 Gross weight: 12.7kg


PALLET EXAMPLE

Height:
 Width: 120cm (std Euro pallet)
 Mepth: 80cm (std Euro pallet)
 Cartons per pallet: 30carton/pallet
 Cartons per row:
 Net weight: 368.808kg
 Gross weight: 381kg

PRODUCT PICTURE



PRODUCT OUTLINE



Avide LED Flood Light Slim SMD 20W NW 4000K

Product code:	ABSSFLNW-20W
Brand link:	avidelighting.com/qr/ABSSFLNW-20W
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-05-21

Page: 3/3

PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.