Datasheet and description



Avide LED T5 Integrated Tube AC Plug 1m

Product code: ABT5-ACPLUG

Brand link: avidelighting.com/qr/ABT5-ACPLUG

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-20

Page: 1/3

SPECIFICATIONS

EAN code: 5999562280089

Warranty: 2year(s)

Working temperature: -20 - + 40 °C

Packaging: 1/b
Certifications: CE

TECHNICAL DETAILS

Wattage:

Voltage: 220-240V

Beam angle:

Dimmability: No

Lumen output:

Color temperature:

Lifetime:

Energy class:

Type of LED: SMD IP standard: IP20

PRODUCT PICTURE



Datasheet and description



Avide LED T5 Integrated Tube AC Plug 1m

Product code: ABT5-ACPLUG

Brand link: avidelighting.com/qr/ABT5-ACPLUG

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-20

Page: 2/3

PRODUCT SIZE

Diameter: Length:

CARDBOARD BOX

EAN: 5999562280089

Packaging: 1/b

Dimensions: 80mm x 195mm x 20mm

Net weight: 37g Gross weight: 48g

CARTON

EAN: 5999562280096

Packaging: 1/b

Dimensions: 380mm x 560mm x 220mm

Net weight: 0.037kg
Gross weight: 0.048kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 1carton/pallet

Cartons per row:

Net weight: 0.037kg
Gross weight: 0.048kg

PRODUCT PICTURE



PRODUCT OUTLINE

Datasheet and description



Avide LED T5 Integrated Tube AC Plug 1m

Product code: ABT5-ACPLUG

Brand link: avidelighting.com/qr/ABT5-ACPLUG

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-20

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED integrated dust- and moisture-proof fixtures represent the modern versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes 3 different lengths and brightness levels, available in neutral white color temperature and with an opaline cover. The 60cm fixture has 20W power, while the 120 centimeter version has a 40W and the 150 centimeter type a 60W power output respectively.